



Product Data Sheet:

SNOWMOBILE OIL SYN 2T

Product Description:

SNOWMOBILE OIL SYN 2T is a fully synthetic excellent performance lubricant developed for air & water cooled 2-stroke engines. The special formulation of **SNOWMOBILE OIL SYN 2T** ensures excellent engine protection, cleanliness and low smoke even under extreme operating conditions.

SNOWMOBILE OIL SYN 2T offers very good lubricity against piston scuffing and wear of engine components. The advanced formulation provides exceptional control against engine deposits, exhaust system blocking and extended engine life without power loss, and reduces visible exhaust smoke. Low ash additive technology prevents pre-ignition and spark plug and easy miscibility with gasoline ensure stable homogeneous mixture even at low ambient temperatures.

SNOWMOBILE OIL SYN 2T is recommended for high-powered 2-stroke engines from snowmobiles/scooters operating under different conditions.

SNOWMOBILE OIL SYN 2T is suitable for oil-injection and premix lubrication systems; always follow manufacturer's recommendations for oil-fuel ratio.

SNOWMOBILE OIL SYN 2T is also suitable for 2-stroke engines in all terrain vehicles, motorcycles, lawn mowers and other applications requiring oils of this quality.

Specifications:

Exceeds: API TC, ISO-L-EGD, JASO FD

Property:	Test Method:	Typical Values:
Density @ 15°C	ASTM D4052	864 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D7042	68 mm ² /s
Kinematic Viscosity @ 100°C	ASTM D7042	11 mm ² /s
Viscosity Index	ASTM D2270	>150
Flash Point	ASTM D92	>90°C
Pour Point	ASTM D97	-45°C
Total Base Number	ASTM D2896	1.6 mgKOH/g
Sulphated Ash	ASTM D874	0.13 wt %

Product nr: 4291

Date Issued: 08/08/2011

Date Superseded: 14/10/2010

Revision nr: 01