



## Product Data Sheet

# CHAINSAW OIL 68

### Product Description:

CHAINSAW OIL 68 is a high quality oil specially developed to lubricate the chain of chain saws.

CHAINSAW OIL 68 is based on high quality mineral base oil in combination with an unique additive package to ensure the following properties:

- Very good adhesive strength.
- Excellent lubricating properties, helps to prevent premature chain failure
- Extend working life.
- The specially selected additives also inhibit rust.

CHAINSAW OIL is NOT suitable to lubricate the engine

### Typical Analysis

| Properties            | Unit               | Method     | Typical Value |
|-----------------------|--------------------|------------|---------------|
| ISO VG Class          |                    |            | 68            |
| Density @15°C         | kg/m <sup>3</sup>  | ASTM D4052 | 883           |
| Kin. Viscosity @40°C  | mm <sup>2</sup> /s | ASTM D7042 | 67.8          |
| Kin. Viscosity @100°C | mm <sup>2</sup> /s | ASTM D7042 | 9.0           |
| Viscosity Index       |                    | ASTM D2270 | 99            |
| Flash Point COC       | °C                 | ASTM D92   | >201          |
| Pour Point            | °C                 | ASTM D97   | -18           |

Product Nr: 4500

Date Issued: 28-04-2015

Date Superseded: -

Revision Nr: -