

Product Data Sheet

COMPRESSOR OIL SYNTH 68

Product Description:

COMPRESSOR POWER SYNTH 68 is an advanced fully synthetic ashless air compressor lubricant developed for use in rotary compressors of screw or vane design, reciprocating compressors and centrifugal compressors. **COMPRESSOR POWER SYNTH 68** is suited single or multiple stage rotary screw or vane, centrifugal compressors and reciprocating compressors of various OEMs including Hydrovane, Atlas Copco, Compare, and Worthington.

COMPRESSOR POWER SYNTH 68 is based on high quality Polyalphaolefin (PAO) base oil in combination with an unique additive package to ensure the following properties:

- Outstanding thermo-oxidative stability.
- Excellent anti-wear protection leads to longer oil and equipment life.
- Low varnish and carbon forming tendency help in reducing maintenance cost.
- Extra high viscosity index.
- Excellent low temperature fluidity for use in wide operating temperature range
- Zinc-free formulation ensures excellent filterability by minimizing oil filter blockage in wet condition.
- Excellent low volatility characteristics give low oil.
- Improved surface properties results in very good anti-foaming and air release properties and superior demulsibility.
- Offers excellent protection against rust and corrosion.
- Compatible with mineral lubricants and also with seals and paints normally used with mineral oils.

Exceeds the Specifications of

DIN 51506 VDL; ISO 6743-3-DAB/DAJ

Typical Analysis

Properties		Unit	Method	Typical Value
ISO VG Class				68
Density @15°C		kg/m³	ASTM D40	52 839
Kin. Viscosity @100°C		mm²/s	ASTM D70	42 7.9
Viscosity Index			ASTM D2270 145	
Flash Point COC		°C	ASTM D92 >201	
Pour Point		°C	ASTM D97	-57
FZG A/8, 3/90°C			DIN 51354-2 >12	
Demulsibility @54°C, max		min	DIN 51599	Pass
		·		
Product Nr. 4414	Date Issued: 20 12 2012	Data Superce	dod	Povision Nr.

Product Nr: 4414 | Date Issued: 29-12-2012 | Date Superseded: - | Revision Nr: -