



**Product Data Sheet:**

# HYDRAULIC OIL HMZF 22

## Product Description:

**HYDRAULIC OIL HMZF 22** is a premium quality zinc free anti wear hydraulic oil developed for use in high pressure hydraulic systems operating under varying temperatures where small viscosity changes with fluctuating temperatures are preferred.

**HYDRAULIC OIL HMZF 22** oil is formulated with carefully selected base stocks fortified with additives and a very shear stable viscosity index improver to impart excellent protection towards wear, rust and oxidation. The viscosity improver reduces the viscosity decrease with rising temperatures.

**HYDRAULIC OIL HMZF 22** is formulated with field proven thermally stable, zinc free based anti wear additives.

**HYDRAULIC OIL HMZF 22** provides excellent water demulsibility as well as de-aeration and effectively protects against rust and oxidation.

**HYDRAULIC OIL HMZF 22** can be used in hydraulic systems in stationary and mobile hydraulic systems, as well as for general machine lubrication.

## Specifications:

**Exceeds:** DIN 51524/2 HLP, ISO 11158 HM, AFNOR NFE 48-603 HM, Eaton (Vickers), M-2950-S/ I-286-S

<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
ISO Viscosity Grade	ISO 3448	22
Density @ 15°C	ASTM D4052	866 kg/m <sup>3</sup>
Kinematic Viscosity @ 40°C	ASTM D7042	19.8-24.2 mm <sup>2</sup> /s
Kinematic Viscosity @ 100°C	ASTM D7042	4.3 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	>98
Flash Point (COC)	ASTM D92	>185°C
Pour Point	ASTM D97	-24°C
Air Release Value @ 50°C	DIN 51381	<3 minutes
Demulsibility @ 54°C	DIN 51599	<10 minutes

Product nr: 4364

Date Issued: 21/10/2011

Date Superseded: 24/09/2010

Revision nr: 02