



Product Data Sheet:

SLIDEWAY OIL 32

Product Description:

SLIDEWAY OIL 32 is specially formulated for the lubrication of slide ways on machine tools.

SLIDEWAY OIL 32 is formulated with special additives to impart tackiness and adhesiveness.

SLIDEWAY OIL 32 overcomes stick-slip motion associated with slow moving parts.

SLIDEWAY OIL 32 can be used on all horizontal and vertical slide ways where a good quality lubricant is required for protection of the slide ways.

SLIDEWAY OIL 32 has good demulsifying properties and protects slide ways against staining and corrosion.

Specifications:

Exceeds: ISO 19378-L-GA/GB, DIN 51502: CGLP, AFNOR E 60-203 L-G, GM: LS-2: LW-1-04, Light MAG Industrial Automation Systems, LLC (Previously known as Cincinnati Machine): P-53

| Property: | Test Method: | Typical Values: |
|---------------------------------|--------------|------------------------|
| ISO Viscosity Grade | ISO 3448 | 32 |
| Density @ 15°C | ASTM D4052 | 874 kg/m ³ |
| Kinematic Viscosity @ 100°C | ASTM D7042 | 7.5 mm ² /s |
| Viscosity Index | ASTM D2270 | 95 |
| Flash Point | ASTM D92 | 180°C |
| Pour Point | ASTM D97 | -21°C |
| Total Acid Number (TAN) | ASTM D974 | 0.4 mgKOH/g |
| Copper Corrosion, 3 hrs @ 100°C | ASTM D130 | 1b max. |

Product nr: 4367

Date Issued: 23/12/2011

Date Superseded: 21/07/2010

Revision nr: 01