



Product Data Sheet:

SLIDEWAY OIL 68

Product Description:

SLIDEWAY OIL 68 is specially formulated for the lubrication of slide ways on machine tools.

SLIDEWAY OIL 68 is formulated with special additives to impart tackiness and adhesiveness.

SLIDEWAY OIL 68 overcomes stick-slip motion associated with slow moving parts.

SLIDEWAY OIL 68 can be used on all horizontal and vertical slide ways where a good quality lubricant is required for protection of the slide ways.

SLIDEWAY OIL 68 has good demulsifying properties and protects slide ways against staining and corrosion.

Specifications:

Exceeds: ISO 19378-L-GA/GB, DIN 51502: CGLP, AFNOR E 60-203 L-G, GM: LS-2: LW-06-1-04, Medium MAG Industrial Automation Systems, LLC (Previously known as Cincinnati Machine): P-47

Property:	Test Method:	Typical Values:
ISO Viscosity Grade	ISO 3448	68
Density @ 15°C	ASTM D4052	885 kg/m ³
Kinematic Viscosity @ 100°C	ASTM D7042	8.7 mm ² /s
Viscosity Index	ASTM D2270	95
Flash Point	ASTM D92	180°C
Pour Point	ASTM D97	-15°C
Total Acid Number (TAN)	ASTM D974	0.4 mgKOH/g
Copper Corrosion, 3 hrs @ 100°C	ASTM D130	1b max.

Product nr: 4368

Date Issued: 23/12/2011

Date Superseded: 21/07/2010

Revision nr: 01