



Product Data Sheet:

SLIDEWAY OIL 220

Product Description:

SLIDEWAY OIL 220 is specially formulated for the lubrication of slide ways on machine tools.

SLIDEWAY OIL 220 is formulated with special additives to impart tackiness and adhesiveness.

SLIDEWAY OIL 220 overcomes stick-slip motion associated with slow moving parts.

SLIDEWAY OIL 220 can be used on all horizontal and vertical slide ways where a good quality lubricant is required for protection of the slide ways.

SLIDEWAY OIL 220 has good demulsifying properties and protects slide ways against staining and corrosion.

Specifications:

Exceeds: ISO 19378-L-GA/GB, DIN 51502: CGLP, AFNOR E 60-203 L-G, GM LS-2: LW-22-1-04, Heavy MAG Industrial Automation Systems, LLC (Previously known as Cincinnati Machine): P-50

Property:	Test Method:	Typical Values:
ISO Viscosity Grade	ISO 3448	220
Density @ 15°C	ASTM D4052	898 kg/m ³
Kinematic Viscosity @ 100°C	ASTM D7042	18.7 mm ² /s
Viscosity Index	ASTM D2270	95
Flash Point	ASTM D92	240°C
Pour Point	ASTM D97	-18°C
Total Acid Number (TAN)	ASTM D974	0.4 mgKOH/g
Copper Corrosion, 3 hrs @ 100°C	ASTM D130	1b max.

Product nr: 4369

Date Issued: 23/12/2011

Date Superseded: 21/07/2010

Revision nr: 01