



Product Data Sheet:

SLIDEWAY OIL 150

Product Description:

SLIDEWAY OIL 150 is specially formulated for the lubrication of slide ways on machine tools.

SLIDEWAY OIL 150 is formulated with special additives to impart tackiness and adhesiveness.

SLIDEWAY OIL 150 overcomes stick-slip motion associated with slow moving parts.

SLIDEWAY OIL 150 can be used on all horizontal and vertical slide ways where a good quality lubricant is required for protection of the slide ways.

SLIDEWAY OIL 150 has good demulsifying properties and protects slide ways against staining and corrosion.

Specifications:

Exceeds: ISO 19378-L-GA/GB, DIN 51502: CGLP, AFNOR E 60-203 L-G

Property:	Test Method:	Typical Values:
ISO Viscosity Grade	ISO 3448	150
Density @ 15°C	ASTM D4052	894 kg/m ³
Kinematic Viscosity @ 100°C	ASTM D7042	15.3 mm ² /s
Viscosity Index	ASTM D2270	>95
Flash Point	ASTM D92	>240°C
Pour Point	ASTM D97	<-18°C
Total Acid Number (TAN)	ASTM D974	<0.95 mgKOH/g
Copper Corrosion, 3 hrs @ 100°C	ASTM D130	1b max.

Product nr: 4495

Date Issued: 17/04/2012

Date Superseded: -

Revision nr: -