



**Product Data Sheet:**

# FORM OIL 10

**Product Description:**

**FORM OIL 10** is a concrete mould oil for the construction of houses, buildings, subways and bridges.

**FORM OIL 10** is based on high-grade refined base oils containing non-toxic surface-active compounds and together with the bleeding water from the concrete, it provides a low interfacial surface tension, which gives a smooth surface finish.

**FORM OIL 10** is ready to use, and should be applied as thin as possible on the surface.

**FORM OIL 10** enables easy removal from the moulds without damaging the concrete and gives a good rust protection of the steel moulds under normal condition. Has good release characteristics and gives no discolouring of the concrete-surface and can be used where limited heated moulds are adapted.

Appliance in a thin layer, by spraying, swabbing or brushing.

Over spill must be removed.

**Specifications:**

Exceeds: -

<b>Property:</b>	<b>Test Method:</b>	<b>Typical Values:</b>
ISO Viscosity Grade	ISO 3448	10
Density @ 15°C	ASTM D4052	850 kg/m <sup>3</sup>
Kinematic Viscosity @ 40°C	ASTM D7042	8-12 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	>95
Flash Point	ASTM D92	>140°C
Pour Point	ASTM D97	<-24°C

Product nr: 4390

Date Issued: 07/05/2012

Date Superseded: 21/07/2010

Revision nr: 01